

# FS700 Series

## Unmanaged Ethernet Switches

The Allied Telesis FS700 Series is the economical and eco-friendly solution for today's IT networks, providing an extensive range of cost-effective options.



### Eco Friendly



The Allied Telesis FS700 Series of eco-friendly switches conforms with Allied Telesis' commitment to environmentally friendly processes and products. They are designed to minimize power consumption through the use of a high-efficiency power supply and a low-power chipset.

The FS700 Series supports Energy Efficient Ethernet (EEE), which automatically reduces the power consumed by the switch whenever there is no traffic on a port. This sophisticated feature can significantly reduce your operating costs by reducing the power requirements of the switch and any associated cooling equipment.

With low power consumption and a reduction in power during after-work hours (overnight mode) – as well as other power saving features included as standard, the FS700 Series truly lives up to its name as “eco-friendly” switches.

Not only does this help the planet by reducing the carbon footprint of each switch, it also lowers the Total Cost of Ownership (TCO) to the organization, as the product costs less to run, and has improved reliability.

### High Performance

Providing powerful 10/100 switching solutions for desktop and small network environments, the FS700 Series of unmanaged switches features full auto-negotiating 10/100 ports. These ports enable the switches to detect the speed and duplex modes of attached devices, enabling them to automatically configure for the best possible performance.

### Flexibility

Available as 5-, 8-, 16- or 24-port models, the FS700 Series meets a multitude of power requirements with both internal and external power-supply options. Also, wall, desk- and rack-mounting options give users ultimate flexibility in selecting the model that meets their physical deployment requirements.

### Simplified Installation

Fully auto-configuring FS700 Series switches require minimal set-up by the user. Auto-sensing ports enable seamless and simple connectivity between existing 10Mbps Ethernet and 100Mbps Fast Ethernet UTP devices—and all units can be installed in minutes. Every FS700 Series model is equipped with MDI/MDI-X ports for simple connection to other hubs and switches. The PoE switches provide wall-mount, rack-mount and desktop options giving users their choice of deployment locations. Finally, easy-to-read front panel LEDs show ongoing switch status and simplify troubleshooting.

## Key Features

- ▶ Wirespeed technology
- ▶ Non-blocking architecture
- ▶ Auto-negotiation ports
- ▶ Auto MDI/MDI-X ports
- ▶ Transparent to VLAN packets
- ▶ Half- and full-duplex flow control
- ▶ External power supply
- ▶ Sturdy metal case

### Quality and Reliability

Allied Telesis is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches each year, Allied Telesis offers proven reliability and industry-recognized quality.

### PoE

The AT-FS708/POE and AT-FS708LE/POE feature automatic detection and classification of an attached PoE device. These small form factor, unmanaged switches are the perfect solution for a wireless security or conference room application.

Specifications

Physical Specifications

PRODUCT	WIDTH	DEPTH	HEIGHT	MOUNTING	PSU	WEIGHT
AT-FS705L	35 mm (1.40 in)	160 mm (6.30 in)	116 mm (4.60 in)	Wall/desktop-mount	Internal	0.50 kg (1.10 lb)
AT-FS705LE	116 mm (4.56 in)	70 mm (2.77 in)	25 mm (1.00 in)	Wall/desktop-mount	External	0.22 kg (0.49 lb)
AT-FS708	36 mm (1.40 in)	249 mm (9.80 in)	116 mm (4.60 in)	Wall/desktop-mount	Internal	0.90 kg (2.00 lb)
AT-FS708/POE	265 mm (10.40 in)	162 mm (6.40 in)	43 mm (1.70 in)	Rack-mount	Internal	1.90 kg (4.20 lb)
AT-FS708LE	130 mm (5.12 in)	70 mm (2.77 in)	25 mm (1.00 in)	Wall/desktop-mount	External	0.27 kg (0.60 lb)
AT-FS708LE/POE	171 mm (6.73 in)	98 mm (3.86 in)	29 mm (1.14 in)	Rack-mount	External	0.43 kg (0.95 lb)
AT-FS7161L	184 mm (7.24 in)	124 mm (4.88 in)	44 mm (1.73 in)	Wall/desktop-mount	Internal	0.80 kg (17.6 lb)
AT-FS724L	280 mm (11.02 in)	180 mm (7.08 in)	44 mm (1.73 in)	Rack-mount	Internal	1.59 kg (3.51 lb)

Performance

PRODUCT	THROUGHPUT	MAC ADDRESS	SWITCHING CAPACITY	PACKET BUFFER
AT-FS705L	0.74Mpps	2K	1Gbps	384K
AT-FS705LE	0.74Mpps	2K	1Gbps	128K
AT-FS708	1.19Mpps	1K	1.6Gbps	768K
AT-FS708/POE	1.19Mpps	8K	1.6Gbps	768K
AT-FS708LE	1.19Mpps	4K	1.6Gbps	256K
AT-FS708LE/POE	1.19Mpps	1K	1.6Gbps	96KB
AT-FS7161L	2.38Mpps	8K	3.2Gbps	160K
AT-FS724L	3.57Mpps	8K	4.8Gbps	160K

\* Half/full-duplex, Auto negotiation, Auto MDI/MDI-X on all ports

LEDs

STATUS INDICATORS	LED	COLOR	DESCRIPTION	FS705L	FS705LE	FS708	FS708/POE	FS708LE	FS708LE/POE	FS716L	FS724L
System Power	Power	Green	Power on	■	■	■	■	■	■	■	■
		Off	Power off	■	■	■	■	■	■	■	■
Link/Activity	L/A / LINK / ACT	Green	Connected at 100Mbps							■	■
		Green (Blinking)	Activity at 100Mbps							■	■
		Amber	Connected at 10Mbps							■	■
		Amber (Blinking)	Activity at 10Mbps							■	■
		Green	Connected	■	■	■	■	■	■		
		Green (Blinking)	Activity	■	■	■	■	■	■		
		Off	No valid link	■	■	■	■	■	■	■	■
Speed	SPD / 100M	Green	Connected at 100Mbps	■	■	■	■	■	■		
		Off	Connected at 10Mbps	■	■	■	■	■	■		
Duplex	DPX / FDX	Green	Full-duplex mode	■	■	■	■	■		■	■
		Green (Blinking)	Collision							■	■
		Off	Half-duplex mode	■	■	■	■	■		■	■
PoE	PoE	Green	PoE device connected				■		■		
			PoE error (no power being supplied)				■ (Green Blinking)		■ (Red)		
		Off	No valid PoE device connected				■		■		

\* Not all LED functions available on all switches

## FS700 Series | Unmanaged Ethernet Switches

### Power Characteristics

PRODUCT	FREQUENCY
AT-FS705L	3.3V/2A
AT-FS705LE	7.5vDC, 1A
AT-FS708/POE	3.3V/2A
AT-FS708LE	7.5vDC, 1A
AT-FS708LE/POE	48V, 1A

\* All models are 50 to 60Hz

#### AT-FS716L

Voltage	100 ~ 240 VAC
Frequency	50/60 Hz
Max Power Consumption	4.67W

#### AT-FS724L

Voltage	100 ~ 240 VAC
Frequency	50/60 Hz
Max Power Consumption	6.72W

#### AT-FS708

Voltage	100 ~ 240 VAC
Frequency	0/60 Hz
Max Power Consumption	3.34W

### PoE Power

#### AT-FS708/POE

Power requirements	90-240V AC
Power consumption	90W max
PoE power	48vDC, 65W
Switch power	12vDC, 20W
AC voltage/frequency requirements:	100 - 240 VAC, 50/60 Hz
AC input power consumption:	Eco friendly mode enabled with no PoE power 6.4 W maximum
Eco-friendly mode enabled with max PoE power 79.2 maximum	

#### PoE power

Available Power over Ethernet: 65 W @ 48vDC
IEEE 802.3af Class 3 (15.4 W): Max 4 ports
IEEE 802.3af Class 2 (7.3 W): Max 8 ports
IEEE 802.3af Mode: Alternative A (MDI)

#### AT-FS708LE/POE

Power requirements	100 – 240V AC
Power consumption	39.2W max
PoE power	48vDC, 30W
AC voltage/frequency requirements:	100 - 240 VAC, 50/60 Hz

#### PoE power:

Available Power over Ethernet: 30W @ 48vDC
IEEE 802.3af Class 3 (15.4 W): Max 2 ports
IEEE 802.3af Class 2 (7.3 W): Max 4 ports
IEEE 802.3af Mode: Alternative A (MDI)

### Interface Connections

10/100TX	RJ-45
100MB or 1000MB SFP	(AT-FS708/POE only)

### Standards and Compliance

IEEE 802.3	10T Ethernet
IEEE 802.3u	100TX Fast Ethernet
IEEE 802.3x	Flow control
IEEE 802.3af	Power over Ethernet, mode A (PoE units)

### Electrical/Mechanical Approvals

UL 1950
CSA 22.2 No. 950 FCC/EN55022 Class B
VCCI Class B
EN60950 (TUV)
EN55024
CE
PoE units:
UL1950 TUV UL
C-Tick CE Mark FCC Part 15
CISPR 22
EN55022

### Ordering Information

#### AT-FS705L-xx

5-port 10/100TX unmanaged switch with internal power supply

#### AT-FS705LE-xx

5-port 10/100TX low power unmanaged switch with external power supply

#### AT-FS708-xx

8-port 10/100TX unmanaged switch with internal power supply

#### AT-FS708/POE-xx

8-port 10/100TX unmanaged PoE switch with 1 SFP

#### AT-FS708LE-xx

8-port 10/100TX low power unmanaged switch with external power supply

#### AT-FS708LE/POE-xx

8-port 10/100TX eco-friendly unmanaged PoE switch

#### AT-FS7161L-xx

16-port 10/100TX unmanaged switch with internal power supply

#### AT-FS724L-xx

24-port 10/100TX unmanaged switch with internal power supply

Where xx =	10 for US power cord
	20 for no power cord
	30 for UK power cord
	40 for Australian power cord
	50 for European power cord

### SFP Modules - AT-FS708/POE

#### AT-SPSX

1000SX GbE multi-mode 850 nm fiber up to 550 m

#### AT-SPFX/2

100FX multi-mode 1310 nm fiber up to 2 km

#### AT-SPLX10

1000LX GbE single-mode 1310 nm fiber up to 10 km

#### AT-SPLX40

1000LX GbE single-mode 1310 nm fiber up to 40 km